



## **GO 1.6 power battery pack**

### **High-power & autonomy battery pack for individual urban light electric vehicles**



Great flexibility

- + CAN 2.0
- + Up to 3 batteries in parallel (with the Forsee Power Switching box)



High reliability and safety

- + Advanced BMS with passive balancing and precharge function
- + Optimized thermal dissipation
- + Robust aluminum casing
- + Best-in-class 18650 cells



Easily swappable

- + Top handle
- + Rack connector at the bottom of the battery pack

# GO 1.6 power Li-ion NMC battery

PHYSICAL SPECIFICATIONS	CONDITIONS	UNIT	MODULE
<b>VOLTAGE</b>			
Minimal	-	V	38.5
Nominal	-	V	50.4
End of charge	-	V	58.8
<b>CURRENT @25°C</b>			
Maximum peak discharge current	≤ 10 sec	A	120
Typical average discharge current	Continuous	A	60
Typical average charge current		A	30
<b>ENERGY @25°C</b>			
Energy	-	Wh	1,512
Energy density	-	Wh/L	208
Capacity	@ 0.2 C discharge	Ah	30
<b>DIMENSIONS</b>			
Height		mm	74
Width		mm	252
Depth without connectors		mm	-
Depth with connectors and handle		mm	380
Weight		kg	11.5
<b>ADDITIONAL INFORMATION @25°C</b>			
Cell configuration	-		14S 10P
Communication protocol			CAN 2.0
Typical number of cycles until 70% of the original capacity	@ discharge rate of 0.2C	cycles	≥ 700
Typical temperature range	Discharge	°C	-20 to 60
	Charge	°C	0 to 45
Certification	UN 38.3		
	CE		
Protection rating	Built to meet		IP65
Option : switching box allowing to use three batteries in parallel or sequentially one after the other			

The information contained herein is provided solely for the purposes of general explanation and illustration, and is subject to modification without notice. No warranty or guarantee is given in regards to the information contained herein or the referenced products. Please contact FORSEE POWER for the most current and relevant product information for your particular application. Version : June 2020